
HURRICANE ANCHOR for DOUBLE TOP PLATE

U.S. Patent Application No. 14/908.536A Canadian Patent Application No. 2956685

"The best new product that has entered the building industry in the last 10 years"
- Nick Bruin, Multiple Master Builder Award Winner

Burmon combines its patented Hurricane Anchors with Impact Driver technology to deliver the most efficient and effective roof truss/rafter tie down system available, saving time and money.



USING BURMON HURRICANE ANCHORS GIVES YOU THE ADVANTAGE:

- Code Compliant - 2012 International Residential Code (IRC) & 2012 International Building Code
- Designed and engineered to resist 96% of all global high wind events
- Anchors can be fixed to top plate whilst on the ground first, making it safer and faster when working at heights
- No toe nailing required
- No hand nailing required
- Stronger, faster connection
- Anchors hold trusses in position making bracing easier and safer


EASY TO INSTALL

1 POSITION



Position BHB anchor at the set out point on the top plate.

2 FIX



Screw fix BHB anchor to top plate with Burmon screws

3 SECURE



Screw fix roof truss/rafter each side to BHB anchor using Burmon screws

Burmon Building Products

CANADA
Toll Free **1-800-369-6380**
www.burmon.com

burmon
HURRICANE ANCHOR

U.S. Patent Application No. 14/908.536A Canadian Patent Application No. 2956685

SPECIFICATION

STEEL

Gauge	18
Corrosion Finish	G90


SCREWS


Burmon screws comply to 1000 hours Salt Spray Testing



BURMON STOCK CODE

BHBDP





1. To achieve twice the capacities for Burmon Anchors, use two anchors fixed one in front of the other on a minimum 6 inch wide top plate.
2. Minimum quantity of fasteners to be installed. Product has additional screw holes not needed to meet published allowable load of product.
3. To view code report, please visit our website **www.burmon.com/code-reports** or visit the code evaluation agency's website.

burmon			FASTENER SCHEDULE				Installation type	Limit State Design DF/SP Factored Resistance (K_D = 1.15)			Limit State Design S-P-F Factored Resistance (K_D = 1.15)			Corrosion Finish
			Truss/Rafter		Double Plate									
Burmon Stock No.	Ref No.	Steel Gauge	Qty	Type Burmon Screws	Qty	Type Burmon Screws	One Anchor	Uplift 160%	Lateral F1 160%	Lateral F2 160%	Uplift 160%	Lateral F1 160%	Lateral F2 160%	Galvanising
BHBDP	BHB	18	6 (3 each side)	BHH39	4	BSD65	k/N	9.4	5.3	4.3	6.6	3.7	3.03	G90
							lbs	2112	1203	971	1484	846	682	
BHBDP	BHB	18	8 (4 each side)	BHH39	6	BSD65	k/N	14.1	8.03	6.4	9.9	5.6	4.5	G90
							lbs	3169	1806	1457	2225	1268	1023	